



**“Master Your Terrain”**  
**(307) – 775 – 9565**  
**[www.tntcustoms.com](http://www.tntcustoms.com)**

## **REAR COIL SPRING RELOCATORS TJ/LJ WRANGLER**

### **Installation Instructions:**

Thank you for purchasing TNT Rear Coil Spring Relocators for your Jeep Wrangler. Please observe proper shop safety procedures when performing this install. Use proper eye and hearing protection as required and use safe jack stands/supports, placed appropriately for supporting the vehicle while you work on it if needed. We recommend pre-fitting all parts before painting them.

#### **STEP 1:**

Begin by raising the rear of the vehicle, unbolting the shocks and disconnecting the rear swaybar.

#### **STEP 2:**

Remove the coil springs.

#### **STEP 3:**

Pull out the rubber bump-stop and unbolt the bump-stop cup.



**STEP 4:**

Bolt the new coil mount in place, tab facing inside, using the provided 10mm X 1-1/2" bolt.



**STEP 5:**

Place one of the included straps over the frame rail and run two 3/8" x 5-1/2" bolts and washers through the strap and through the coil mount. Install 3/8" nuts and washers.



**STEP 6:**

Using the provided 3/8" X 1-1/4" bolts, nuts and washers, install the provided coil mount plate, bump-stop cup and bump-stop. For a factory wheelbase setup, use the furthest forward hole. If wheelbase has been adjusted rearward, we provide you with two additional mounting holes to choose from depending on your application.



**STEP 7:**

Reinstall your coil springs, shocks and reconnect the swaybar.

**Appendix A****Parts List:**

- 1 – Drivers side coil spring relocater.
- 2 – Passenger side coil spring relocater.
- 3 – (2) Coil spring mounting plates.
- 4 – (2) Frame straps

**Hardware Kit:**

- 1 – 4 ea., 3/8" X 5" bolts, nuts, washers
- 2 – 2 ea., 3/8" X 1-1/4" bolts, nuts, washers
- 3 – 2 ea., 10mm X 1-1/2" bolts

**TNT**  
**216 Avenue D – Suite A**  
**Cheyenne, WY 82007**  
**(307) – 775 – 9565**  
[www.tntcustoms.com](http://www.tntcustoms.com)